

### EJOT® Frame anchor Type RA-U

Particularly suited for

- Direct installation of plastic and wood windows in brick work and concrete without plug
- Efficient distance installation of windows and doors
- Installation according to the guideline of the RAL association for windows and doors

Also suited for

- Direct fastening in concrete and brick work without plug



40

#### PROPERTIES

- Suited for all frame materials
- Optimal power transference and guide through Torx power drive
- Reduced levelling torques and precise fit due to perfect thread geometry
- High installation performance, safe anchorage
- Durable corrosion protection thanks to high-quality galvanic coating
- Universally usable in all window materials
- Higher durability of screwdriver bits

#### TECHNICAL DATA

Head diameter..... 8.5 mm  
Drive ..... TORX® T30

#### INSTALLATION

- Drill Ø 6.2 mm frame holes at factory or building site, distances according to RAL quality assessment
- Align frames carefully in brick opening
- Drill Ø 6 mm brick holes, drill hole depth = screw-in depth + 10 mm
- Fastening with EJOT frame anchor using standard equipment
- Attach cap if required

#### APPLICATION

Minimum screw-in depth in:  
Concrete..... 30 mm  
Sand-lime stone, solid brick..... 40 mm  
Vertically perforated brick, lightweight concrete, pumice ..... 60 mm

#### ACCESSORIES

Cover cap

Drill hole diameter (mm)	Length in mm	Packing unit (pieces)	Order description
<b>Zinc-plated, blue passivated</b>			
7.5	40	1.200	<b>610 40 60 1</b>
7.5	60	1.200	<b>610 60 60 1</b>
7.5	70	1.200	<b>610 70 60 1</b>
7.5	80	1.200	<b>610 80 60 1</b>
7.5	100	600	<b>611 00 60 1</b>
7.5	120	600	<b>611 20 60 1</b>
7.5	135	400	<b>611 35 60 1</b>
7.5	150	400	<b>611 50 60 1</b>
7.5	180	400	<b>611 80 60 1</b>
7.5	210	400	<b>612 10 60 1</b>

